

## Manufacturer's Safety and Quality Assurance Certificate

This certificate relates only to the individual product detailed below.  
Visit [www.airquee.com](http://www.airquee.com) for more information. **This is the test certificate for your new inflatable. Please keep this in a safe place. This is valid for one year from the date below.**



**Product:** 12X12FT MULTICOLORED PARTY FLOATING BALLOONS  
A FRAME

**Serial/Certificate no:** P66097 **Code:** AQ9814PAMULTI

**Tag No:** N/A

**Valid From:** 28-03-2025

**Weight:** Unit: 56kg Total: 66kg

### Structure

Trough Depth  
Seam Security  
Stitching  
Walls & Towers  
Can Walls Contain Users  
Fall Off Height (FOH)  
Grounding  
Stability  
Entrapment  
Sharp Angles  
Zip(s)  
Windows  
Netting  
Clamber Netting  
Air Loss Points  
Markings  
Artwork  
Identification

Pass	Fail	N/A
X		
X		
X		
X		
X		
X		
X		
X		
X		
X		
		X
X		
		X
X		
X		
X		
X		

### Notes

Indoor Use Only: No  
Label Location: side  
Length: 3.9m  
Width: 3.7m  
Height: 2.95m  
Bed width panel: 0.55  
Trough depth: 0.10  
Inside wall height: 1.05 m  
FOH: 0.47 m  
Grounding weight: 85  
Zips: 3 pcs (exterior velcro flap + interior non return flap)  
Netting: black scrim fixed  
Roof : ice blue gloss 450g PVC  
Artwork : printed (laminated, UV resistant)

### Materials

Fabric Material and Condition  
Thread Condition  
Material Fire Retardancy  
De-lamination of PVC

X		
X		
X		
X		

### Notes

Material : gloss 630g pvc + 520 g printable material

### Anchorage

Total No of Anchors  
Anchor Point Integrity  
Anchor Point Location  
Anchor Type  
Anchor Accessories  
Ropes

X		
X		
X		
X		
X		
		X

### Notes

Calculated Anchors: 6  
Anchor points: 6 pcs PVC & metal triangle Bottom  
Supplied anchor accessories: 6 pcs / 400 mm\* 18 mm metal pegs

### Blower

Kilopascal (kPa)  
Size & Type  
Inlet & Outlet Mesh  
Cable & Plug  
Casing & Impeller  
Pat Test  
Return Flap  
Blower Tube(s) / Valve(s)

X		
X		
X		
X		
X		
		X
X		
X		

### Notes

kPa: 1.17  
Blower minimum pressure: 1.00  
Blower power: 1 pcs 1.5HP  
Blower tube length: 1.23 m  
Position: 1 pcs rear side

### Enterances, Exits & Evacuation

Deflation / Evacuation Time  
Length of Step

X		
X		

### Notes

Evacuation time(secs): 20    Enclosed Unit: Yes    Platform height : 0.68m    Step Length: 1.12m

### Totally Enclosed Structures

Exits  
Exit Markings  
Lighting Supports  
Emergency Lighting  
Deflation Speed  
User Area Pressure

		X
		X
		X
		X
		X
		X

### Notes

### Slides

Wall Height / Platform Height  
Run-Out  
Clamber Step  
Slide Sheet

		X
		X
		X
		X

### Notes

Platform roof fitted: No    Slide sheet: N/A

### Users

Max User Height: 1.8    Max Users upto 1m: 6    Max Users upto 1.25m: 4    Max Users upto 1.5m: 3    Max Users over 1.8: 2

SIGNED BY: Demeter Attila  
PIPA ANNUAL INFLATABLE INSPECTOR

