## **GSB** Inflatable Inspections

## & coolkidsbouncycastles.com



| ANNUAL SAFE                     | _ ' ' | 114 | SFL | CHON REPO                             | Tel: 07928 678577                                       |
|---------------------------------|-------|-----|-----|---------------------------------------|---|
| Structure<br>Security of Seams  | P     | F   | N/A |                                       | 2209  |
| Stitching                       | ~     |     |     |                                       | 1   |
| Anchor Points                   | V     |     |     |                                       | \ 0   |
| Anchor Accessories              | V     |     |     | Manufactured by:                      | 1.6.  |
| Walls & Towers                  | -     |     |     | 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | D   |
| Blower Distance                 | ~     |     |     | Serial Number                         | RusyoIgA  |
| Zip(s)                          | V     |     |     | V                                     | 2018  |
| Fabric Flame Retardant          | V     |     |     | Year Made:                            |   |
| Fabric Strength                 | V     |     |     | Description of Unit:                  | SHOOT OUT CAME  |
| Step/Ramp Size                  | V     |     |     | Description of One.                   |   |
| Grounding                       | ~     |     |     |                                       |   |
| Sharp Angles & Edges            | ~     |     |     |                                       |   |
| Stability                       | ~     |     |     |                                       |   |
| Ropes                           |       |     | /   | Colour                                | Clean WHITE   |
| Artwork to EN71-3?              |       |     |     | Colour:                               |   |
| (Supplier/Importer must provide |       |     |     | Size:                                 | 5.2+32+26m  |
| certificates for new equipment) | V     |     |     | GIEG.                                 |   |
| Air Loss Points                 | ~     |     |     | Max No. Users:                        | 94  |
| Water Gauge Pressure            | ~     |     |     |                                       | 1.84  |
| Fall Off Height                 | V     |     |     | Max User Height:                      |   |
| Trough Depth                    |       |     | 1   | Date Issued:                          | 16th January 2025 TutyFre<br>15th January 2026 ThatySix |
| Thread                          | ~     |     |     | Date issued.                          | . 514 1 5 12  |
| Netting                         | ~     |     |     | Expiry Date:                          | 15th JANLING 2026 That pix                              |
| Entrapment                      | V     |     |     |                                       | ,   |
| Deflation/Evacuation Time       | V     |     |     |                                       |   |
| Windows                         |       |     | V   | Notes/Risk Assessm                    | ent   |
| Markings                        | V     |     |     |                                       |   |
| Identification                  | V     |     |     | CIBBOM 1-5.                           | TERMUND TO  |
| Totally Enclosed Structures     |       |     |     | 4,000                                 | S   |
| Exits                           |       |     |     | 1                                     |   |
| Exit Markings                   |       | 1   |     | 1                                     |   |
| Lighting Supports               |       | /   |     | 1                                     |   |
| Emergency Lighting              |       | K   |     |                                       |   |
| Deflation Speed                 | /     | - 1 |     |                                       |   |
| User Area Pressure              | _     |     |     |                                       |   |
| Slides                          |       |     | 1   |                                       |   |
| Wall Heights                    |       | 1   |     |                                       |   |
| Run Out                         |       | 7   |     |                                       |   |
| Clamber Net                     |       | N   |     |                                       |   |
| Slide Sheet                     |       |     |     |                                       |   |
| Blower                          |       |     |     |                                       |   |
| Size & Type                     | 1     |     |     |                                       |   |
| Inlet & Outlet Mesh             | ~     |     |     |                                       |   |
| Cable & Plug                    | 1     |     |     |                                       |   |
| Casing & Impeller               | ~     |     |     |                                       |   |
| Pat Test                        | 1     |     |     |                                       |   |
| Return Flap                     | -     |     |     |                                       |   |

This annual report confirms the equipment identified above was tested and conformed to EN14960-2019 Standards at the time of test, however it does not confirm the equipment will continue to conform to the above standard for the full 12 months prior to the expity date.

| Signed:  | (,                                    | Bull | Print:   | C. Britte  |  |
|----------|---------------------------------------|------|----------|--|--|
| Sidiled. | · · · · · · · · · · · · · · · · · · · | 10   | 1 111141 | The state of the s |  |